

Breville®




BES980

Replace Tamper Gear Box Assembly







This document is the property of Breville Group which contains confidential and propriety information and is a reference document to be used only by the intended recipient and not shared with other parties. No part of the information may be used or reproduced in anyway without the written consent of Breville Group




Replace Tamper Gear Box Assembly

1.	<p>A. Turn brewer upside down.</p> <p>B. Remove 2 screws from main chassis as shown in picture.</p> <p>C. Remove tamper fan</p>	
2.	<p>A. Turn Tamper Fan Connector clockwise to remove Tamper Fan Connector and shim washers (between 3 to 8 washers).</p> <p>B. Turn Brewer upright.</p>	
3.	<p>Remove 4 screws of rear top cover.</p> <p>Note: Screw marked by arrow is longer than the other screws.</p>	




This document is the property of Breville Group which contains confidential and propriety information and is a reference document to be used only by the intended recipient and not shared with other parties. No part of the information may be used or reproduced in anyway without the written consent of Breville Group

4.	Open top cover and remove rear cover	
5.	A. Remove 2 cable ties, sleeves as mark by red circle. B. Remove 2 Screws from bottom cover. C. Disassemble rear panel bottom cover and fold to the side.	
6.	Release 2 tap at PCB box for open the PCB top cover.	
7.	Remove white wire with white female connector from main PCB as mark by Red circle.	




This document is the property of Breville Group which contains confidential and propriety information and is a reference document to be used only by the intended recipient and not shared with other parties. No part of the information may be used or reproduced in anyway without the written consent of Breville Group

8.	Remove the Close-end Connector and disconnect 3 white wires (2 wires marked by 22 AGW and 1 marked 18 AGW)	
9.	Remove the Close-end Connector and disconnect 2 brown wires.	
10.	Open top housing. Fold it to rear side	

This document is the property of Breville Group which contains confidential and propriety information and is a reference document to be used only by the intended recipient and not shared with other parties. No part of the information may be used or reproduced in anyway without the written consent of Breville Group

11.	Remove Cable Tie from Main PCB Box. (As shown in the picture)	
12.	Remove 3 cable ties above Control Panel. (As shown in the picture)	
13.	Remove 4 cable ties, at steam wound side Panel.	

This document is the property of Breville Group which contains confidential and propriety information and is a reference document to be used only by the intended recipient and not shared with other parties. No part of the information may be used or reproduced in anyway without the written consent of Breville Group

14.	Remove the wires from the 2 hooks beside Auto Tamper Gear Box. (as shown in the picture)	
15.	A. Remove 6 Screws on Gear Box. (as shown in the picture) B. Remove Tamper Gear Box Assembly.	
16.	Hold Augur Head in place While install Tamper Gear Box into Main Chassis.	
17.	Reassemble: - Reverse the procedure from Step 13.	

This document is the property of Breville Group which contains confidential and propriety information and is a reference document to be used only by the intended recipient and not shared with other parties. No part of the information may be used or reproduced in anyway without the written consent of Breville Group