

Breville®





BES980

Americano Solenoid Valve Assembly Replacement







This document is the property of Breville Group which contains confidential and propriety information and is a reference document to be used only by the intended recipient and not shared with other parties. No part of the information may be used or reproduced in anyway without the written consent of Breville Group

Solenoid Assembly replacement

1.	Remove 2 screws near shower head as indicated.	
2.	Remove 4 screws of rear top cover. Note: Screw marked by arrow is longer than the other screws.	
3.	Remove the top and top rear cover	
4.	Open Top Housing. Fold it to the rear Side.	

This document is the property of Breville Group which contains confidential and propriety information and is a reference document to be used only by the intended recipient and not shared with other parties. No part of the information may be used or reproduced in anyway without the written consent of Breville Group

5.	Disconnect 3wires as mark by red circle.	
6.	Remove 2 Screws from Solenoid Valve.	
7.	Remove U-Shape Clips and disconnect Elbow Tubes. . (Marks: The Teflon tube sleeved with Silicone Tube is at terminal side of Solenoid Valve.)	
8.	A. Remove the O-Rings from the Elbow Tubes. B. Assemble O-Rings to new Americano Solenoid valve.	
9.	Reassemble: - Reverse the procedure from Step 7.	

This document is the property of Breville Group which contains confidential and propriety information and is a reference document to be used only by the intended recipient and not shared with other parties. No part of the information may be used or reproduced in anyway without the written consent of Breville Group