

Breville®




BES980

Augur head assembly replacement







This document is the property of Breville Group which contains confidential and propriety information and is a reference document to be used only by the intended recipient and not shared with other parties. No part of the information may be used or reproduced in anyway without the written consent of Breville Group





Augur head assembly replacement

1.	<p>A. Turn brewer upside down.</p> <p>B. Remove 2 screws from main chassis as shown in picture.</p> <p>C. Remove tamper fan</p>	
2.	<p>A. Turn Tamper Fan Connector clockwise to remove Tamper Fan Connector and shim washers (between 3 to 8 washers).</p> <p>B. Turn Brewer upright.</p>	
3.	<p>Remove 4 screws of rear top cover.</p> <p>Note: Screw marked by arrow is longer than the other screws.</p>	





This document is the property of Breville Group which contains confidential and propriety information and is a reference document to be used only by the intended recipient and not shared with other parties. No part of the information may be used or reproduced in anyway without the written consent of Breville Group

4.	Open top cover and remove rear cover	
5.	A. Remove 2 cable ties as mark by red circle. B. Remove 2 Screws from Bottom cover. C. Disassemble Rear Panel Bottom Cover and fold to the side.	
6.	Release 2 tap at PCB box for open the PCB top cover.	
7.	Remove blue wire with white female connector from PCB as mark by Red circle.	

This document is the property of Breville Group which contains confidential and propriety information and is a reference document to be used only by the intended recipient and not shared with other parties. No part of the information may be used or reproduced in anyway without the written consent of Breville Group

8.	Remove the Close-end Connector and disconnect 3 white wires (2 wires marked by 22 AGW and 1 marked 18 AGW)	
9.	Remove the Close-end Connector and disconnect 2 red wires and 1 pink wire.	
10.	Open Top Housing. Fold it to rear side.	
11.	Remove Cable Tie from Main PCB Box. (As shown in the picture)	

This document is the property of Breville Group which contains confidential and propriety information and is a reference document to be used only by the intended recipient and not shared with other parties. No part of the information may be used or reproduced in anyway without the written consent of Breville Group

12.	Remove Cable Tie above Control Panel as shown. (as shown in the picture)	
13.	Remove the wires from the 2 hooks beside Auto Tamper Gear Box. (as shown in the picture)	
14.	A. Remove 6 Screws on Gear Box. (as shown in the picture) B. Remove Tamper Gear Box Assembly.	
15.	A. Remove existing Augur Head Assembly from Main Chassis. B. Replace new Augur Head Assembly	
16.	Reassemble: - Reverse the procedure from Step 13.	

This document is the property of Breville Group which contains confidential and propriety information and is a reference document to be used only by the intended recipient and not shared with other parties. No part of the information may be used or reproduced in anyway without the written consent of Breville Group